

# ***Sports-O-Zone USA, LLC***

## **Sanitizing Unit Features & Requirements**

### **Mechanicals/Dimensions/Maintenance**

- Electric – Std 110/120 volt outlet, Measured max draw 3.5 amps (MRC cycle), Plug GFCI
- Total amps of components – 11.11
- Circuit breakers on components
- Generator specs (mobile service) – recommend inverter series Honda EU2000 or similar spec. Inverter controls fluctuations in energy that can damage the computer board.
- Extension cord – minimum 12 gage, no longer than 100 feet (not included with unit)
- Dimensions/Weight – 66”W x 51”H x 24”D, 400 lbs, total height door open 72”
- Shipping Dimensions/Weight -- 73”W x 61”H x 31”D, 720 lbs
- Doorway – Fits through std 30” door
- Ease of movement: 4 industrial casters with 2 locking casters
- Limited 2 year warranty
- Exterior is stainless steel
- Interior is galvanized steel
- Minimal maintenance (yearly maintenance cost after year two, <\$200)
  - Wipe ozone generation unit with soft cloth every 6-12 months depending on usage
  - Replace ozone monitor sensor once yearly (one replacement sensor is included with each machine at point of purchase)
  - Removable floor for easy vacuum clean up.

### **Capacity**

- 18.7 cubic feet
- Photo capacity of football helmets
- Photo capacity of shoulder pads
- Photo capacity of hockey gear
- Processing capacity:
  - 75-90 helmets/hour
  - 30-45 shoulder pads/hour
- Capacity can vary by size and shape of equipment
- Equipment should be packed loosely in sanitizing unit with ability for ozone to circulate around equipment
- Fabrics/Laundry items should be sanitized separately using Calzone

### **Safety Features**

- Smart Technology controls ozone levels, tracks temperature, humidity levels, and controls all other operating features of various models.
- Electric lock will not release until ozone level is within OSHA limits.
- Illuminated emergency stop button with glow in the dark sign.
  - Shuts off ozone and unlocks the door.
- Ozone shuts off automatically if door is open.
- When the machine is used as directed, it operates within OSHA safety guidelines for ozone.
- GFCI (Ground Fault Circuit Interrupter) plug.
- Component circuit breakers.

### **Operating Features: 4201 (see additional models and their features below)**

- Patented sanitizing system.
- No consumables to purchase.
- Equipment does not get wet.
- Hanging bar for clothing.
- Wire rack.

425 Pine Creek Court, Elkhart, IN 46516 • 877-264-6062

[www.sportsozone.com](http://www.sportsozone.com)

# ***Sports-O-Zone USA, LLC***

## **Sanitizing Unit Features & Requirements**

- Push button operation.
- Total Ozone/Reduction cycle approximately 14 minutes.
- Information download records ozone levels, tracks temperature & humidity levels.

### **Optional Features**

- **Model 4201A**  
Same features as 4201 plus two warm air moisture reduction cycles:
  1. 30 minutes warm air followed by an ozone sanitizing cycle.
  2. 60 minutes warm air followed by an ozone sanitizing cycle.
- **Model 4202**  
Same features as 4201 plus vending capability:
  1. Accepts coupons and bills.
  2. U.S. model accepts \$1.00, \$5.00, \$10.00, and \$20.00 denominations.
  3. Canadian model accepts \$1.00, \$5.00, \$10.00, and \$20.00 denominations.
  4. Vend price can be set in \$1.00 increments from \$1.00-\$99.00.
  5. Information download records coupons & currency transactions.
- **Model 4203** (Only available in United States)  
Same features as 4202 plus wireless credit card reader:
  1. Will accept coupons, bills and/or credit cards.
  2. Information download same as 4202 plus records credit card transactions.